

JC091020



Country Of Origin : Please Contact Customer Service

Niteflood™ LED Floodlight 20W IP65 3000K / 4000K / 5700K CCT Black +PIR

- 3CCT Switchable colour temperature
- 2100 Lumens
- 105 LpcW
- 4000K colour temperature
- IP65 protection of full fitting, including PIR
- Manual override function
- Breather gland protects against condensation
- Opal glass for reduced glare
- Angled bracket for ease of installation
- Supplied pre-wired with 800mm flex
- Driverless technology
- 10 - 2000 Lux adjustable
- 10sec to 7min adjustable 'on' time
- 180° detection
- 1.8m to 2.5m mounting height
- 10m detection at 2.5m
- Independently tested to ISO9227:2022 salt spray test

Technical Information

Electrical

Class : I

Luminaire Circuit Wattage : 20W

Voltage Rating : 220-240

General Information

Additional Information : To operate the manual override function: Turn the power OFF /ON/OFF/ON within 5 seconds. To return to Automatic PIR detection mode: Turn off power for 10 seconds, then turn power ON.If the power is off for longer than 15 seconds the floodlight will light up for 5 seconds before activating automatic PIR detection mode.

Color Finish : Black

IP Rating : IP65

Light Source Features : CCT Switchable

Method of fix : Screws/Rawl plugs

Mounting : Wall Mount

Overall Dimensions : 154.8 x 146.6 x 99.3

Product Group : LED Floodlights



Product Range : Niteflood

Warranty : 3 Year Warranty

Performance Data

Thermals

Actual Lumen Output : 2100	Operating Temperature
Beam Angle ° : 100	Range °C : -10 to 30
CRI: Ra : 83	
Correlated Color	
Temperature : 3000 / 4000 / 5700K	
Lumens Per Circuit Watt : 105	

	
---	---