

JC091022



Country Of Origin : Please Contact
Customer Service

Niteflood™ LED Floodlight 30W IP65 3000K / 4000K / 5700K
CCT Black +PIR

- 3CCT Switchable colour temperature
- 3200 Lumens
- 107 LpcW
- 4000K colour temperature
- IP65 protection of full fitting, including PIR
- Manual override function
- Breather gland protects against condensation
- Opal glass for reduced glare
- Angled bracket for ease of installation
- Supplied pre-wired with 800mm flex
- Driverless technology
- 10 - 2000 Lux adjustable
- 10sec to 7min adjustable 'on' time
- 180° detection
- 1.8m to 2.5m mounting height
- 10m detection at 2.5m
- Independently tested to ISO9227:2022 salt spray test

Technical Information

Electrical

Class : I

Luminaire Circuit Wattage :
30W

Voltage Rating : 220-240

General Information

Additional Information : To operate the manual override function: Turn the power OFF /ON/OFF/ON within 5 seconds. To return to Automatic PIR detection mode: Turn off power for 10 seconds, then turn power ON.If the power is off for longer than 15 seconds the floodlight will light up for 5 seconds before activating automatic PIR detection mode.

Color Finish : Black

IP Rating : IP65

Light Source Features : CCT
Switchable

Method of fix : Screws/Rawl
plugs

Mounting : Wall Mount

Overall Dimensions : 174 x
173.6 x 105.8

Product Group : LED
Floodlights

Product Range : Niteflood

Warranty : 3 Year Warranty

Performance Data

Thermals

Actual Lumen Output : 3200

Operating Temperature

CRI: Ra : 83

Range °C : -10 to 30

Correlated Color

Temperature : 3000 / 4000 /

5700K

Lumens Per Circuit Watt : 107

© Copyright 2024 JCC